

TEL.

(800) 727-9262

(800) 727-9957

(213) 747-4500

(213) 747-3234



Finish:

Lens:

ARCHITECTURAL GRADE SERIES

## SPECIFICATION SHEET

E-Mail: sales@coronalighting.com

PRODUCT #: CL-226-AB

•Well Lights

Cast Brass

**Fixture Specifications:** 

Housing: **Cast Brass** 

AB-Antique Bronze, Faceplate Natural toning

process. AB finish will vary due to artistic process.

Also available in SS finish.

Clear, tempered and heat resistant convex glass.

Extra flat lens included.

Socket: Top grade ceramic bi-pin socket with retention

clip.

Lamp: 12V, MR-16, 50W max.

> Available in LED (3.5W & 5W) or without lamp. See the Lamp Guide below for more information.

Gasket: Silicone "0" ring seals faceplate to housing

providing weather tight protection.

Fixture is prewired with a 3-ft 18-2 SJT-W direct Wiring:

burial cord. Wire connector sold seperately. Silicone filled direct buirial wire nut (CX-854) is

available from Corona Lighting.

Mounting: In-ground direct burial or concrete encasement.

**Electrical Notes:** A remote 12V transformer is required. Options are


available from Corona Lighting.

Voltage range for LED lamps are 9V-17V. Proper grease/lubricant is suggested on threaded parts during installation process.

Warranty: Limited lifetime warranty on brass fixture

against manufacturer's defects.





DATE:

TYPE:

PRODUCT #: **TOTAL QUANTITY:** 

TRANSFORMER: CONTRACTOR: SPECIFIER:

JOB NAME & ADDRESS:

LAMP TYPE & WATTAGE:

AVAILABLE LED LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)	JOB INFORMATION

3.5W and 5W

		BEAM		COLOR &	RATED	HALOGEN
LAMP NUMBER	WATTS	SPREAD	LUMEN	TEMP.	HOURS	EQUIVALENT
L-ED16-3W-SP	3.5	15° Spot	270	2700K	50,000	25 Watt
L-ED16-3W-FL	3.5	45° Flood	270	2700K	50,000	25 Watt
L-ED16-3W-WF	3.5	60° Wide Flood	270	2700K	50,000	25 Watt
L-ED16-5W-SP	5	15° Spot	350	2700K	50,000	40 Watt
L-ED16-5W-FL	5	45° Flood	350	2700K	50,000	40 Watt
L-ED16-5W-WF	5	60° Wide Flood	350	2700K	50,000	40 Watt
L-ED16-COB5W-SP	5	15° Spot	450	2700K	50,000	50 Watt
L-ED16-COB5W-FL	5	38° Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-WF	5	60° Wide Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-SP3K	5	15° Spot	470	3000K	50,000	50 Watt
L-ED16-COB5W-FL3K	5	38° Flood	470	3000K	50,000	50 Watt
L-ED16-COB5W-WF3K	5	60° Wide Flood	470	3000K	50,000	50 Watt

■ Single color MR-16 LED available in AMBER, BLUE, GREEN, PURPLE, RED and VIOLET

• CL - product # - lamp - wattage - lamp angle

• When ordering LED lamp with a fixture your part number should follow the format below:

Example: CL-226-AB-L-ED16-5W-FL FL CL - 226-AB - L-ED16 - 5W -



ARCHITECTURAL GRADE SERIES

**ACCESSORIES SHEET** 

1633 Staunton Ave Los Angeles, CA 90021

TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

PRODUCT #: CL-226-AB

• Well Lights

• Cast Brass

## **Cable Connector**

CX-854 Direct Burial Silicone Filled Wire Nut, Tan



## Special Lenses & Honeycomb Louvers

CX-238	MR-16 Snap-on holder, Silver Plated
CX-239	MR-16 honeycomb louver, Black
CX-240-AM	MR-16 color lens, Amber
CX-240-BL	MR-16 color lens, Blue
CX-240-GR	MR-16 color lens, Green
CX-240-RD	MR-16 color lens, Red
CX-240-YL	MR-16 color lens, Yellow
CX-241	MR-16 lens, Linear Spread
CX-242	MR-16 lens, Frosted
CX-243	MR-16 lens, Prismatic

For MR-16 Lenses and Louvers, you will need the CX-238

