

SPECIFICATION SHEET

 1633 Staunton Ave

 Los Angeles, CA 90021

 TEL.
 FAX.

 (800) 727-9262
 (800) 727-9957

 (213) 747-4500
 (213) 747-3234

E-Mail: sales@coronalighting.com

1

	DUCT #		-			•Direct	tional Ligh	is •	Aluminum
Fixture	Specif	icatio	ons:						
Housing:	Die-cast alur	minum.				Gaske	t:	Silicone "O" ring seals f	face plate to housing providin
Finish:	Polyester U\	/ powde	r coated, availab	ole in BK -	Black			weather-tight protection	n.
Lens:	Clear, tempe gasket.	ered and	heat resistant g	lass with s	silicone	Knuck	le:		ble knuckle with a phillips I threaded male hub on botto
Socket:	-	eramic b	i-pin socket, with	n retentior	ı clip.	Mount	ing Spike:	8" Black ABS spike with hub.	n ½" NPT threaded female
Lamp:		LED (3.	ax. 5W & 5W) or witl e below for more			Electri	cal Notes:	available from Corona Voltage range for LED	lamps are 9V-17V.
Wiring:	burial cord. Universal co	Wire co onnector	vith a 3ft 18-2 SF nnector sold sep (CX-839) and si ailable from Corc	erately. licone fille	d wire	Warrar	nty:	Proper grease/lubrican threaded parts during in One (1) year warranty of manufacturer's defects	nstallation process. on fixture and housing agains
			*						
AVAILABI		MPS (Co	rona LED lamps have	a five (5) ye		E D V and 5			37/8"→
		,	BEAN	1	ar limited warrar	nty against man	ufacturer's defect		8
LAMP NU		WATTS	BEAM	LUMEN	ar limited warrar _ COLOR & TEMP.	nty against man RATED HOURS	ufacturer's defect HALOGEN EQUIVALEN		8
	LE LED LAN JMBER -SP	,	BEAN	1	ar limited warrar	nty against man	ufacturer's defect		ON DATE:
LAMP NU -ED16-3W -ED16-3W	LE LED LAN JMBER -SP -FL	WATTS 3.5	BEAM SPREAD 15° Spot	1 LUMEN 270	ar limited warrar COLOR & TEMP. 2700K	nty against man RATED HOURS 50,000	ufacturer's defect HALOGEN EQUIVALEN 25 Watt		ON DATE:
LAMP NU -ED16-3W -ED16-3W -ED16-3W -ED16-5W	LE LED LAN JMBER -SP -FL -WF -SP	WATTS 3.5 3.5 3.5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot	LUMEN 270 270 270 350	ar limited warrar - COLOR & TEMP. 2700K 2700K 2700K 2700K	nty against man RATED HOURS 50,000 50,000 50,000 50,000	Mufacturer's defect HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt 40 Watt		ON DATE:
-ED16-3W -ED16-3W -ED16-3W -ED16-5W -ED16-5W	LE LED LAN JMBER -SP -FL -WF -SP -FL	WATTS 3.5 3.5 3.5 5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood	LUMEN 270 270 270 270 350 350	ar limited warrar - COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K	nty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000	All of the second secon	s) JOB INFORMATIO	ON DATE:
LAMP NI -ED16-3W -ED16-3W -ED16-5W -ED16-5W -ED16-5W -ED16-5W	UMBER -SP -FL -WF -FL -WF	WATTS 3.5 3.5 3.5 5 5 5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood	LUMEN 270 270 270 350 350 350	ar limited warrar COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K	nty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000	Ufacturer's defect HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt	s) JOB INFORMATIO	ON DATE: SS:
LAMP NI -ED16-3W -ED16-3W -ED16-5W -ED16-5W -ED16-5W -ED16-CO	LE LED LAN JMBER -SP -FL -WF -SP -FL -WF B5W-SP	WATTS 3.5 3.5 3.5 5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood	LUMEN 270 270 270 270 350 350	ar limited warrar - COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K	nty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000	All of the second secon	s) JOB INFORMATIO	ON DATE: SS:
LAMP NI ED16-3W ED16-3W ED16-5W ED16-5W ED16-5W ED16-CO ED16-CO	UMBER -SP -FL -WF -SP -FL -WF B5W-SP B5W-FL	WATTS 3.5 3.5 3.5 5 5 5 5 5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot	LUMEN 270 270 270 270 350 350 350 350 450	ar limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K	nty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000	ufacturer's defect HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt 40 Watt 50 Watt	s) JOB INFORMATIO	ON DATE: SS:
LAMP NU ED16-3W ED16-3W ED16-5W ED16-5W ED16-5W ED16-CO ED16-CO ED16-CO	UMBER -SP -FL -WF -SP -FL -WF B5W-SP B5W-FL	WATTS 3.5 3.5 3.5 5 5 5 5 5 5 5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood	LUMEN 270 270 270 270 350 350 350 450 450	ar limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K	nty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	All of the second secon	s) JOB INFORMATIO	ON DATE: SS:
LAMP NU ED16-3W ED16-3W ED16-5W ED16-5W ED16-CO ED16-CO ED16-CO ED16-CO ED16-CO	LE LED LAN JMBER -SP -FL -WF -SP -FL -WF B5W-SP B5W-FL B5W-WF	WATTS 3.5 3.5 3.5 5 5 5 5 5 5 5 5	BEAN SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood 60° Wide Flood	LUMEN 270 270 270 350 350 350 350 450 450 450	ar limited warrar COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K	nty against man RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	Autorer's defect HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt 40 Watt 50 Watt 50 Watt 50 Watt	s) JOB INFORMATIO	ON DATE: SS:

•CL - product # - lamp - wattage - lamp angle

CL - 511-BK - L-ED16 - 5W - FL Example: CL-511-BK-L-ED16-5W-FL

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



ACCESSORIES SHEET

PRODUCT # : CL-511

Mounting Pedestals

Ground Spikes

CX-642-BK

CX-642-BZ

CX-643-BZ

CX-646-BK

CX-646-BR CX-646-SS

CX-647-BK

CX-601-BK	1" PVC Mounting Pedestal, 1/2" NPT, Black
CX-601-VG	1" PVC Mounting Pedestal, 1/2" NPT, Verde Green
CX-603-BK	3" PVC Mounting Pedestal, ½" NPT Female Brass Hub on top, Black
CX-603-VG	3" PVC Mounting Pedestal, ½" NPT Female Brass Hub on top, Verde Green
	40"



CX-603-BK

CX-604-BK	1" PVC Adjustable Mounting Pedestal, ½" NPT, Black
CX-621-BK	1" PVC Cap, ½" NPT, Black
CX-621-VG	1" PVC Cap, 1/2" NPT, Verde Green
CX-622-BK	2" PVC Cap, ½" NPT, Black
CX-622-VG	2" PVC Cap, 1/2" NPT, Verde Green
CX-624-BK	3" PVC Cap, ½" NPT Female Brass Hub, Black
CX-624-VG	3" PVC Cap, ½" NPT Female Brass Hub, Verde Green

1633 Staunton Ave Los Angeles, CA 90021 TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

```
•Directional Lights
```

Aluminum

Mounting Canopies

CX-701-BK	Aluminum Round Canopy , ½ NPT, Black
CX-702-BK	Aluminum Rectangular Canopy, ½ NPT, Black
CX-703	Aluminum tree mount canopy ½ NPT Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green, WH- White
CX-720	Aluminum Tree mount Canopy with 9" Rubber Strap stretches to 14" Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green, WH- White
CX-721	Aluminum Tree mount Canopy with 15" Rubber Strap stretches to 22" Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
CX-722	Aluminum Tree mount Canopy with 22" Rubber Strap stretches to 33" Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green, WH- White
CX-723	Aluminum Tree mount Canopy with 31" Rubber Strap stretches to 45" Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White

Mounting Risers

<u>↓</u> <u>4¹/2"</u> <u>↓</u>	СХ-722-ВК	CX-671	6" Aluminum Riser, ½ NPT Male/Female Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
CX-703-BK	6	CX-672	12" Aluminum Riser, ½ NPT Male/Female Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green, WH- White
8.5" ABS Spike, ½" NPT, Black 8.5" ABS Spike, ½" NPT, Bronze 8.5" ABS Spike, ½" NPT, Bronze	→ 3"→	CX-673	18" Aluminum Riser, ½ NPT Male/Female Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
10½"	→ ▶		СХ-671-ВК 6″
СХ-647-ВК			CX-672-BK 12"
8" ABS Spike, ½" NPT, Black			
8" ABS Spike, ½" NPT, Natural Brass			CX-673-BK 18"
8" ABS Spike, ½" NPT, Stainless Stee	I		
10.5" Heavy Duty ABS Spike, ½" NPT,	Black		



ACCESSORIES SHEET

•Directional Lights

1633 Staunton Ave Los Angeles, CA 90021 TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

Aluminum

PRODUCT # : CL-511

Mounting Brackets

wounting	Brackets	Sher
CX-700	Aluminum Bracket with ½" NPT	CX-23
	Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green,	CX-23
	WH- White	CX-24
CX-704	Aluminum Oval Bracket with 1/2" NPT Female Hub	CX-24
	Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green,	CX-24
	WH- White	CX-24
		CX-24
СХ-700-ВК		CX-24
	21/2"	CX-24
		CX-24
	<u> </u>	• For N
	3"►	
	·	
	СХ-704-ВК	
	1%"	
	← 2 ³ / ₄ " →	
Cable Cor	nnectors	
CX-854	Direct Burial Silicone Filled Wire Nut, Tan	
CX-858	Speedy Cable Connector, Supply Cable up to 10-2, Black	
CX-839	Universal cable connector, Supply cable up to 8-2,	
	one/Pack Black	
	CV 030	
	CX-839	
	1¼"	

Special Lenses & Honeycomb Louvers 38 MR-16 Snap-on holder, Silver Plated 239 MR-16 honeycomb louver, Black 40-AM MR-16 color lens, Amber 240-BL MR-16 color lens, Blue 240-GR MR-16 color lens, Green 40-RD MR-16 color lens, Red 40-YL MR-16 color lens, Yellow 241 MR-16 lens, Linear Spread 42 MR-16 lens, Frosted 43 MR-16 lens, Prismatic

• For MR-16 Lenses and Louvers, you will need the CX-238





11/4"-