

SPECIFICATION SHEET

 1633 Staunton Ave

 Los Angeles, CA
 90021

 TEL.
 FAX.

 (800) 727-9262
 (800) 727-9957

 (213) 747-4500
 (213) 747-3234

E-Mail: sales@coronalighting.com

1

 Lens: Clear, tempered and heat resistant glass with silicone gasket. Socket: Top grade ceramic bi-pin socket, with retention clip. Lamp: 12V, MR-16, 50W max. Available in LED (3.5W & 5W) or without lamp. See the Lamp Guide below for more information. Knuckle: Cast aluminum adjustabke knuckle with a phillips shaped screw. ½" NPT threaded male hub on botto botto shaped screw. ½" NPT threaded female hub. Electrical Notes: A remote 12V transformer is required. Options are available from Corona Lighting. Voltage range for LED lamps are 9V-17V. Proper grease/lubricant is suggested on 	FR 1 //								ts		
Housing: Die-cast aluminum. Gasket: Silicone 'C' ing seals face plate to housing providi Finish: Polyester UV powder coated, available in BK-Black. Gasket: Silicone 'C' ing seals face plate to housing providi Gasket: Clear, tempered and heat resistant glass with silicone gasket. Gasket: Silicone 'C' ing seals face plate to housing providi Gasket: Tog grade caramic bi-pin socket, with retention clip. Gasket: Silicone 'C' ing seals face plate to housing providi Amp: Tog grade caramic bi-pin socket, with retention clip. Gasket: Silicone 'C' ing seals face plate to housing providi See the Lamp Guide below for more information. Mirrise Fature is previned with a 31 f18-2 SPT1-W direct Gasket: Aremote 12V transformer is required. Options are available from Corona Lighting. Cickaes All are available from Corona Lighting. Warranty: On (1) year warranty on fature and housing again matteriater's defect. Warranty: So St and SD So Warrant's defect. So Warrant's defect. Warranty: So St and SD So Warrant's defect. So Warrant's defect. Warranty: So St and SD So Warrant's defect. So Warrant's defect. Woltage range of LED LAMPS (coust LED LAMPS (coust LED to MSN with set to	FROL		T . C								
Finish: Polyseter UV powder coated, available in BK- Black Lens: Weather-light protection. Clear, tempered and heat resistant glass with silicone gasket. Clear, tempered and he	Fixture	e Specif	icatio	ons:							
Initian: Polyster UP provider coated, available in BK-Black Lens: Creat: tempered and heat resistant glass with silicon gasket. Socket: Top grade caramic bi-pin socket, with retention clip. Creat: Advailable in LED (38W & 6W) or without tamp. See the Lamp Cuide below for more information. Mounting Spike: 8' Black AdS spike with 's' NPT threaded female hub. Wiring: Future and silicone filde wire nut (CX-684) are available from Corona Lighting. Electrical Notes: Arealable from Corona Lighting. Warranty: Outgage range for LED 1400 and silicone filde wire nut (CX-684) are available from Corona Lighting. Warranty: One (1) year warranty on fixture and housing again manufacturer's defects WMILABLE LED LAMPS (Corona LED tamps have a five (5) year tambe tamps to the Silicon filde wire not (CIX-684) are available from Corona Lighting. Yarranty: Old INFORMATION VMILABLE LED LAMPS (Corona LED tamps have a five (5) year tambe tamps to gask to mark tamps to the Silicon filde wire not (CIX-684) are available from Corona Lighting. Yarranty: Old INFORMATION VMILABLE LED LAMPS (Corona LED tamps have a five (5) year tambe tamps to gask to more throng tamps to gask to more tamps to more tamps to more tamps to gask to m	Housing:	Die-cast alu	minum.				Gasket		÷ .	plate to housing p	providin
Lens: Clear. tempered and heat resistant glass with silicone gasket. shaped screw. ½" NPT threaded male hub on bottom gasket. Socket: Tog grade ceramic bi-pin socket, with retention clip. amp: Analysia in LEG (35 kW 5 W) or without lamp. See the Lamp Guide below for more information. Image: Clear and the clear information. Wiring: Exit is previded with a 3th 18-2 SPT 1-W direct built of CM. Wire concerts old separately. Universal connector (CK 383) and silicone filled wire nut (CK 384) are available from Corona Lighting. Warranty: One (1) year warranty on fixture and housing again manufacturer's defects Warranty: One (1) year warranty on fixture and housing again manufacturer's defects Socket: Tog 376", Socket: Tog 376", Tog 376", Socket: Tog 376", Socket: Tog 376", Tog 376", Socket: Tog 376", To	Finish:		•				Knuckle	ə:	0 1	knuckle with a phi	illips
Socket: Tog grade ceramic bi-pin socket, with retention clip. hub. .amp: 12V, MR-16, 50W max. Available in LED (35W & 5W) or without lamp. See the Lamp Guide below for more information. Niring: Fitter is previde with with and 18:02-SPT-1W direct burial cord. With connector sold separately. Universal control (VS-839) and silcone filled with en.tt. (CX-854) are available from Corona Lighting. Corona Lighting. Warranty: One of the connector sold separately. Universal control (VS-839) and silcone filled with en.tt. (CX-854) are available from Corona Lighting. Warranty: One of the connector sold separately. Universal control (VS-839) are available from Corona Lighting. Warranty: One of the connector sold separately. Universal control (VS-839) are available from Corona Lighting. Warranty: One of the connector sold separately. Universal control (VS-839) are available from Corona Lighting. Warranty: One of the connector sold separately. Universal control (VS-839) are available from Corona Lighting. Warranty: One of the connector sold separately. Universal control (VS-839) are available from Corona Lighting. Wall_ABLE_LED_LAMPS (coons_LED langes have a five (9) per filted warranty separater manufacturer's defects OB INFORMATION Lamp Number Mark Socket Mark Socket Mark Mark Socket M	Lens:		ered and	l heat resistant g	lass with s	ilicone			shaped screw. 1/2" NPT thre	aded male hub o	n botto
Available in LED (3.5W & SW) or without lamp. available from Corona Lighting. available from Corona Lighting. Wiring: Fixture is prewired with a 3t 18-2 SPT1-W direct burial cord. Wire connector sold separately. Universal concert (CX-4354) are available from Corona Lighting. Warranty: available from Corona Lighting. Warranty: Warranty: Warranty: Warranty: The add parts during installation process. One (1) year warranty on fixture and housing again maufacturer's defects Wire connector (SX-439) are available from Corona Lighting. Warranty: Warranty: The add parts during installation process. Wire connector (SX-439) are available from Corona Lighting. Warranty: The add parts during installation process. Wire connector (SX-439) are available from Corona Lighting. Warranty: The add parts during installation process. Wire connector (SX-439) are available from Corona Lighting. Warranty: The add parts during installation process. Wire connector (SX-439) are available from Corona Lighting. Warranty: The (1) year warranty on fixture and housing again maufacturer's defects Wire connector (SX-439) are available from Corona Lighting. The connector state add parts during installation process. The connector state add parts during installation process. Wire connector (SX-439) are available from Corona Lighting. The connector state add parts du	Socket:	Top grade c	eramic b	i-pin socket, with	retention	clip.	wountin	ід эріке:		NP1 threaded ten	nale
Wiring: Exture is prewrited with a 3ft 13-2 SPT1-W direct connector (CX-839) and silicone filled wire nut (CX-854) are available from Corona Lighting. Warranty: threaded parts during installation process. Warranty: Warranty: One (1) year warranty on fixture and housing again manufacture's defects Warranty: Warranty: One (1) year warranty on fixture and housing again manufacture's defects Warranty: Warranty: One (1) year warranty on fixture and housing again manufacture's defects Warranty: Warranty: One (1) year warranty on fixture and housing again manufacture's defects Warranty: Signa (1) year warranty on fixture and housing again manufacture's defects Image: Signa (1) year warranty on fixture and housing again manufacture's defects Warranty: Signa (1) year warranty on fixture and housing again manufacture's defects Image: Signa (1) year warranty on fixture and housing again manufacture's defects Warranty: Signa (1) year warranty on fixture and housing again manufacture's defects Image: Signa (1) year (1) year Warranty: Signa (1) year warranty on fixture and housing again manufacture's defects Image: Signa (1) year (1) year Warranty: Signa (1) year Signa (1) year Image: Signa (1) year (1) year Tellos: Signa (1) year Signa (1) year Signa (1) year <td< td=""><td>Lamp:</td><td>Available in</td><td>LED (3.</td><td>5W & 5W) or with</td><td></td><td>n.</td><td>Electric</td><td>al Notes:</td><td>available from Corona Lighti Voltage range for LED lamps</td><td>ing. s are 9V-17V.</td><td>s are</td></td<>	Lamp:	Available in	LED (3.	5W & 5W) or with		n.	Electric	al Notes:	available from Corona Lighti Voltage range for LED lamps	ing. s are 9V-17V.	s are
$\begin{tabular}{ c c c c c c c c c c c c c c c c c c c$	Wiring:	burial cord.	Wire co	nnector sold sep	erately. Un		Warran	ty:	threaded parts during install One (1) year warranty on fix	lation process.	agains
Image: Non-Section of the Section of Sectin of Section of Section of Section of Section of Section				60					33/4" 37/8	ν γ	
LAMP NUMBER WATTS BEAM COLOR & SPREAD RATED HOURS HALOGEN EQUIVALENT TYPE: DATE: -ED16-3W-SP 3.5 15° Spot 270 2700K 50,000 25 Watt JOB NAME & ADDRESS: JOB NAME & ADDRESS: -ED16-3W-VFF 3.5 60° Wide Flood 270 2700K 50,000 25 Watt JOB NAME & ADDRESS: -ED16-SW-SP 5 15° Spot 350 2700K 50,000 40 Watt PRODUCT #: -ED16-SW-SP 5 15° Spot 350 2700K 50,000 40 Watt TOTAL QUANTITY: -ED16-SW-WF 5 60° Wide Flood 350 2700K 50,000 50 Watt TOTAL QUANTITY: -ED16-COB5W-SP 5 15° Spot 450 2700K 50,000 50 Watt TAMP TYPE & WATTAGE: -ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TANSFORMER: -ED16-COB5W-WF 5 60° Wide Flood 2700K 50,000 50 Watt TANSFORMER: TRANS								3			
LAMP NUMBER WATTS SPREAD LUMEN TEMP. HOURS EQUIVALENT TYPE: DATE: -ED16-3W-SP 3.5 15° Spot 270 2700K 50,000 25 Watt JOB NAME & ADDRESS:						L 3.5V	ED V and 5V			-3 ⊛	7/8"→
ED16-3W-SP 3.5 15° Spot 270 270K 50,000 25 Watt JOB NAME & ADDRESS: ED16-3W-WF 3.5 45° Flood 270 270K 50,000 25 Watt PRODUCT #: ED16-3W-WF 3.5 60° Wide Flood 270 270K 50,000 25 Watt PRODUCT #: ED16-5W-SP 5 15° Spot 350 270K 50,000 40 Watt TOTAL QUANTITY: ED16-5W-WF 5 60° Wide Flood 350 270K 50,000 50 Watt TOTAL QUANTITY: ED16-COB5W-SP 5 15° Spot 450 270K 50,000 50 Watt LAMP TYPE & WATTAGE: ED16-COB5W-FL 5 38° Flood 450 270K 50,000 50 Watt LAMP TYPE & WATTAGE: ED16-COB5W-SP3K 5 15° Spot 450 270K 50,000 50 Watt TANSFORMER: ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR: ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt CONTRACTOR: <th>VAILABL</th> <th></th> <th>MPS (co</th> <th>prona LED lamps have</th> <th>a five (5) yea</th> <th></th> <th></th> <th>N</th> <th>B"</th> <th>-3</th> <th>7/8-</th>	VAILABL		MPS (co	prona LED lamps have	a five (5) yea			N	B "	-3	7/8-
HED16-3W-FL 3.5 45° Flood 270 2700K 50,000 25 Watt HED16-3W-WF 3.5 60° Wide Flood 270 2700K 50,000 25 Watt HED16-SW-SP 5 15° Spot 350 2700K 50,000 40 Watt PRODUCT #: HED16-SW-VFL 5 45° Flood 350 2700K 50,000 40 Watt TOTAL QUANTITY: HED16-COB5W-SP 5 15° Spot 450 2700K 50,000 50 Watt LAMP TYPE & WATTAGE: HED16-COB5W-FL 5 60° Wide Flood 450 2700K 50,000 50 Watt LAMP TYPE & WATTAGE: HED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt LAMP TYPE & WATTAGE: HED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: HED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR: HED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt CONTRACTOR:				BEAM		r limited warran	nty against manua	facturer's defect	S" JOB INFORMATION		7/8
ED16-5W-SP 5 15° Spot 350 2700K 50,000 40 Watt PRODUCT #: ED16-5W-FL 5 45° Flood 350 2700K 50,000 40 Watt TOTAL QUANTITY: ED16-COB5W-SP 5 15° Spot 450 2700K 50,000 50 Watt LAMP TYPE & WATTAGE: ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: ED16-COB5W-FL 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: ED16-COB5W-FL 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR: ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt CONTRACTOR:	LAMP NL -ED16-3W-	LE LED LA	WATTS	BEAM SPREAD 15° Spot	LUMEN	r limited warran COLOR & TEMP. 2700K	nty against manua RATED HOURS	ALOGEN HALOGEN EQUIVALEN 25 Watt	S JOB INFORMATION TYPE:		
ED16-5W-FL 5 45° Flood 350 2700K 50,000 40 Watt TOTAL QUANTITY: ED16-SW-WF 5 60° Wide Flood 350 2700K 50,000 40 Watt TOTAL QUANTITY: ED16-COB5W-SP 5 15° Spot 450 2700K 50,000 50 Watt LAMP TYPE & WATTAGE: ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: ED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR: ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt CONTRACTOR:	LAMP NL ED16-3W- ED16-3W-	LE LED LA	WATTS 3.5 3.5	BEAM SPREAD 15° Spot 45° Flood	LUMEN 270 270	r limited warran COLOR & TEMP. 2700K 2700K	nty against manual RATED HOURS 50,000 50,000	ALOGEN HALOGEN EQUIVALEN 25 Watt 25 Watt	S JOB INFORMATION TYPE:		7/8"-
ED16-5W-WF 5 60° Wide Flood 350 2700K 50,000 40 Watt TOTAL QUANTITY: ED16-COB5W-SP 5 15° Spot 450 2700K 50,000 50 Watt LAMP TYPE & WATTAGE: ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: ED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR: ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt CONTRACTOR:	LAMP NL ED16-3W- ED16-3W- ED16-3W-	LE LED LA	WATTS 3.5 3.5 3.5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood	LUMEN 270 270 270 270	r limited warran COLOR & TEMP. 2700K 2700K 2700K	nty against manual RATED HOURS 50,000 50,000 50,000	ALOGEN HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt	S) JOB INFORMATION TYPE: JOB NAME & ADDRESS:		
ED16-COB5W-FL 5 38° Flood 450 2700K 50,000 50 Watt TRANSFORMER: ED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR: ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt CONTRACTOR:	LAMP NL ED16-3W ED16-3W ED16-3W	LE LED LA JMBER -SP -FL -WF -SP	WATTS 3.5 3.5 3.5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot	LUMEN 270 270 270 270 350	r limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K	nty against manual RATED HOURS 50,000 50,000 50,000 50,000	ALOGEN Facturer's defect HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt 25 Watt 40 Watt	S) JOB INFORMATION TYPE: JOB NAME & ADDRESS:		
ED16-COB5W-WF 5 60° Wide Flood 450 2700K 50,000 50 Watt TRANSFORMER: -ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR: -ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt CONTRACTOR:	ED16-3W- ED16-3W- ED16-3W- ED16-3W- ED16-5W- ED16-5W-	LE LED LA JMBER -SP -FL -WF -SP -FL -SP -FL	WATTS 3.5 3.5 3.5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood	270 270 270 270 350 350	r limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K	nty against manual RATED HOURS 50,000 50,000 50,000 50,000 50,000	ALOGEN HALOGEN EQUIVALEN 25 Watt 25 Watt 25 Watt 40 Watt 40 Watt	S) JOB INFORMATION TYPE: JOB NAME & ADDRESS: PRODUCT #:		
ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR: ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt CONTRACTOR:	LAMP NL -ED16-3W- -ED16-3W- -ED16-3W- -ED16-5W- -ED16-5W- -ED16-5W-	JMBER -SP -FL -WF -FL -WF	WATTS 3.5 3.5 3.5 5 5 5 5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood	LUMEN 270 270 270 350 350 350	r limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K	nty against manual RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000	An of the second	S) JOB INFORMATION TYPE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY:		
-ED16-COB5W-FL3K 5 38° Flood 470 3000K 50,000 50 Watt	LAMP NL -ED16-3W- -ED16-3W- -ED16-3W- -ED16-5W- -ED16-5W- -ED16-CO -ED16-CO	JMBER -SP -FL -WF -FL -WF B5W-SP B5W-SP B5W-FL	WATTS 3.5 3.5 3.5 5 5 5 5 5 5 5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood	LUMEN 270 270 270 350 350 350 450 450	r limited warran COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K	nty against manual RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	An end of the second se	S) JOB INFORMATION TYPE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE:		
	LAMP NU -ED16-3W- -ED16-3W- -ED16-5W- -ED16-5W- -ED16-5W- -ED16-COI -ED16-COI -ED16-COI -ED16-COI	JMBER -SP -FL -WF -SP -FL -WF B5W-SP B5W-SP B5W-FL B5W-WF	WATTS 3.5 3.5 5 5 5 5 5 5 5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood 60° Wide Flood	LUMEN 270 270 270 350 350 350 450 450 450	r limited warrant COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K	nty against manual RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	A Constraints of the second se	S JOB INFORMATION TYPE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE: TRANSFORMER:		
	LAMP NU -ED16-3W- -ED16-3W- -ED16-5W- -ED16-5W- -ED16-5W- -ED16-COI -ED16-COI -ED16-COI -ED16-COI	JMBER -SP -FL -WF -SP -FL -WF B5W-SP B5W-FL B5W-SP3K	WATTS 3.5 3.5 5 5 5 5 5 5 5 5 5 5 5	BEAM SPREAD 15° Spot 45° Flood 60° Wide Flood 15° Spot 45° Flood 60° Wide Flood 15° Spot 38° Flood 60° Wide Flood	LUMEN 270 270 270 350 350 350 450 450 450 470	r limited warrant COLOR & TEMP. 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 2700K 3000K	nty against manual RATED HOURS 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000 50,000	An of the second	S JOB INFORMATION TYPE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE: TRANSFORMER:		

•CL - product # - lamp - wattage - lamp angle

CL - 513-BK - L-ED16 - 5W - FL Example: CL-513-BK-L-ED16-5W-FL

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



ACCESSORIES SHEET

PRODUCT # : CL-513

Mounting Pedestals

CX-601-BK	1" PVC Mounting Pedestal, ½" NPT, Black
CX-601-VG	1" PVC Mounting Pedestal, 1/2" NPT, Verde Green
CX-603-BK	3" PVC Mounting Pedestal, ¹ / ₂ " NPT Female Brass Hub on top, Black
CX-603-VG	3" PVC Mounting Pedestal, ¹ / ₂ " NPT Female Brass Hub on top, Verde Green
	▲18"



CX-604-BK	1" PVC Adjustable Mounting Pedestal, ½" NPT, Black
CX-621-BK	1" PVC Cap, ½" NPT, Black
CX-621-VG	1" PVC Cap, 1/2" NPT, Verde Green
CX-622-BK	2" PVC Cap, ½" NPT, Black
CX-622-VG	2" PVC Cap, 1/2" NPT, Verde Green
CX-624-BK	3" PVC Cap, ½" NPT Female Brass Hub, Black
CX-624-VG	3" PVC Cap, 1/2" NPT Female Brass Hub, Verde Green

1633 Staunton Ave Los Angeles, CA 90021 TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

```
    Directional Lights
```

• Aluminum

Mounting Canopies

-	-
CX-701-BK	Aluminum Round Canopy , ½ NPT, Black
CX-702-BK	Aluminum Rectangular Canopy, ½ NPT, Black
CX-703	Aluminum tree mount canopy ½ NPT Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
CX-720	Aluminum Tree mount Canopy with 9" Rubber Strap stretches to 14" Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
CX-721	Aluminum Tree mount Canopy with 15" Rubber Strap stretches to 22" Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
CX-722	Aluminum Tree mount Canopy with 22" Rubber Strap stretches to 33" Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White
CX-723	Aluminum Tree mount Canopy with 31" Rubber Strap stretches to 45" Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White

Mounting Risers

	CX-671	6" Aluminum Riser, ½ NPT Male/Female Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green, WH- White	
8	CX-672	12" Aluminum Riser, ½ NPT Male/Female Finishes: BK - Black, BZ - Bronze, GR - Green, GT - Granite, RT - Rust, VG - Verde Green, WH - White	
-	CX-673	18" Aluminum Riser, ½ NPT Male/Female Finishes: BK- Black, BZ- Bronze, GR- Green, GT- Granite, RT- Rust, VG- Verde Green, WH- White	
		СХ-671-ВК 6	, '
		СХ-672-ВК 12	2'
	the second statement of the se		

	СХ-647-ВК
CX-646-BK	8" ABS Spike, ½" NPT, Black
CX-646-BR	8" ABS Spike, ½" NPT, Natural Brass
CX-646-SS	8" ABS Spike, ½" NPT, Stainless Steel

8.5" ABS Spike, 1/2" NPT, Black

8.5" ABS Spike, 1/2" NPT, Bronze

8.5" ABS Spike, 1/2" NPT, Bronze

101/2"

Ground Spikes

CX-642-BK

CX-642-BZ

CX-643-BZ

CX-647-BK 10.5" Heavy Duty ABS Spike, ½" NPT, Black

СХ-722-ВК



ACCESSORIES SHEET

1633 Staunton Ave Los Angeles, CA 90021 FAX. TEL. (800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

Aluminum

PRODUCT # : CL-513

Mounting Brackets

	DIACKEIS	opec
CX-700	Aluminum Bracket with ½" NPT Finishes: BK - Black, BZ- Bronze, GR- Green,	CX-23 CX-23
	GT - Granite, RT - Rust, VG - Verde Green, WH - White	CX-24
CX-704	Aluminum Oval Bracket with ½" NPT Female Hub	CX-24
	Finishes: BK - Black, BZ - Bronze, GR - Green,	CX-24
	GT- Granite, RT - Rust, VG - Verde Green, WH- White	CX-24
		CX-24
СХ-700-ВК		CX-24
	21/2"	CX-24
		CX-24
		• For N
◀──	3"►	
	СХ-704-ВК	
		3
Cable Con	nectors	
СХ-854 [Direct Burial Silicone Filled Wire Nut, Tan	
CX-858 S	Speedy Cable Connector, Supply Cable up to 10-2, Black	
	Universal cable connector, Supply cable up to 8-2,	
(one/Pack Black	
	CX-839	
	1¼"	
	*	

Special Lenses & Honeycomb Louvers

•Directional Lights

•	2
CX-238	MR-16 Snap-on holder, Silver Plated
CX-239	MR-16 honeycomb louver, Black
CX-240-AM	MR-16 color lens, Amber
CX-240-BL	MR-16 color lens, Blue
CX-240-GR	MR-16 color lens, Green
CX-240-RD	MR-16 color lens, Red
CX-240-YL	MR-16 color lens, Yellow
CX-241	MR-16 lens, Linear Spread
CX-242	MR-16 lens, Frosted
CX-243	MR-16 lens, Prismatic

MR-16 Lenses and Louvers, you will need the CX-238





