

(800) 727-9262 (213) 747-4500

(800) 727-9957 (213) 747-3234

(WWW.CORONALIGHTING.COM

ARCHITECTURAL GRADE SERIES

## SPECIFICATION SHEET

E-Mail: sales@coronalighting.com

## PRODUCT #: CL-528B-GM

Cast Brass

### **Fixture Specifications:**

Housing & Shroud: Corrosion Resistant Cast Brass.

Finish: GM-Gun Metal. Natural toning process.

GM finish will vary due to artistic process.

Also available in AB- Antique Bronze finish

Lens: Clear and heat resistant convex glass.

Socket: Top grade fixed ceramic bi-pin socket, with lamp

retension clip to securely hold lamp in place.

Lamp: 12V, MR-16, 35W max.

Available in LED (3.5W & 5W) or without lamp. See the Lamp Guide below for more information.

Wiring: Fixture is prewired with a 3-ft 18-2 SPT2-W direct

burial cord. Wire connector sold seperately.

Universal connector (CX-839) and silicone filled wire nut (CX-854) are available from Corona Lighting.

Directional Lights

Gasket: Silicone double gasketed for water tight sealing

Knuckle: Adjustable cast brass knuckle with thumb screw

and 1/2" NPT threaded male hub on bottom.

Mounting Spike: Standard injection molded spike with ½" NPT

threaded female hub.

Electrical Notes: A remote 12V transformer is required. Options are

available from Corona Lighting.


Voltage range for LED lamps are 9V-17V. Proper grease/lubricant is suggested on threaded parts during installation process.

Limited lifetime warranty on fixture housing against Warranty:

manufacturer's defects.







|  |       | BEAM           |       | COLOR & | RATED  | HALOGEN    |
|--|-------|----------------|-------|---------|--------|------------|
| LAMP NUMBER  | WATTS | SPREAD         | LUMEN | TEMP.   | HOURS  | EQUIVALENT |
| L-ED16-3W-SP   | 3.5   | 15° Spot       | 270   | 2700K   | 50,000 | 25 Watt    |
| L-ED16-3W-FL   | 3.5   | 45° Flood      | 270   | 2700K   | 50,000 | 25 Watt    |
| L-ED16-3W-WF   | 3.5   | 60° Wide Flood | 270   | 2700K   | 50,000 | 25 Watt    |
| L-ED16-5W-SP   | 5     | 15° Spot       | 350   | 2700K   | 50,000 | 40 Watt    |
| L-ED16-5W-FL   | 5     | 45° Flood      | 350   | 2700K   | 50,000 | 40 Watt    |
| L-ED16-5W-WF   | 5     | 60° Wide Flood | 350   | 2700K   | 50,000 | 40 Watt    |
| L-ED16-COB5W-SP  | 5     | 15° Spot       | 450   | 2700K   | 50,000 | 50 Watt    |
| L-ED16-COB5W-FL  | 5     | 38° Flood      | 450   | 2700K   | 50,000 | 50 Watt    |
| L-ED16-COB5W-WF  | 5     | 60° Wide Flood | 450   | 2700K   | 50,000 | 50 Watt    |
| L-ED16-COB5W-SP3K  | 5     | 15° Spot       | 470   | 3000K   | 50,000 | 50 Watt    |
| L-ED16-COB5W-FL3K  | 5     | 38° Flood      | 470   | 3000K   | 50,000 | 50 Watt    |
| L-ED16-COB5W-WF3K  | 5     | 60° Wide Flood | 470   | 3000K   | 50,000 | 50 Watt    |
| Single color MR-16 LED available in AMBER, BLUE, GREEN, PURPLE, RED and VIOLETghting.com |       |                |       |         |        |            |

JOB INFORMATION

TYPE: DATE:

**JOB NAME & ADDRESS:** 

PRODUCT #:

**TOTAL QUANTITY:** 

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

• When ordering LED lamp with a fixture your part number should follow the format below:

• CL - product # - lamp - wattage - lamp angle CL - 528B-GM - L-ED16 - 5W -FL

Example: CL-528B-GM-L-ED16-5W-FL



WWW.CORONALIGHTING.COM

ARCHITECTURAL GRADE SERIES

# **ACCESSORIES SHEET**

1633 Staunton Ave Los Angeles, CA 90021

FAX. (800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

Cast Brass

## PRODUCT #: CL-528B-GM

#### **Mounting Pedestals**

CX-601-BK 1" PVC Mounting Pedestal, 1/2" NPT, Black

CX-601-VG 1" PVC Mounting Pedestal, 1/2" NPT, Verde Green

3" PVC Mounting Pedestal, 1/2" NPT Female Brass Hub CX-603-BK

on top, Black

CX-603-VG 3" PVC Mounting Pedestal, 1/2" NPT Female Brass Hub

on top, Verde Green



1" PVC Adjustable Mounting Pedestal, 1/2" NPT, Black CX-604-BK

1" PVC Cap, 1/2" NPT, Black CX-621-BK

CX-621-VG 1" PVC Cap, 1/2" NPT, Verde Green

CX-622-BK 2" PVC Cap, 1/2" NPT, Black

CX-622-VG 2" PVC Cap, 1/2" NPT, Verde Green

CX-624-BK 3" PVC Cap, 1/2" NPT Female Brass Hub, Black

3" PVC Cap, 1/2" NPT Female Brass Hub, Verde Green CX-624-VG

### Directional Lights

**Ground Spikes** 

CX-642-BK 8.5" ABS Spike, 1/2" NPT, Black

CX-642-BZ 8.5" ABS Spike, 1/2" NPT, Bronze

CX-643-BZ 8.5" ABS Spike, 1/2" NPT, Bronze



CX-647-BK

CX-646-BK 8" ABS Spike, 1/2" NPT, Black

8" ABS Spike, 1/2" NPT, Natural Brass CX-646-BR

CX-646-SS 8" ABS Spike, 1/2" NPT, Stainless Steel

CX-647-BK 10.5" Heavy Duty ABS Spike, 1/2" NPT, Black

#### **Mounting Risers**

CX-682B-GM 6" Brass Riser, ½ NPT Male/Female, **Gun Metal** CX-683B-GM 12" Brass Riser, ½ NPT Male/Female, Gun Metal CX-684B-GM 18" Brass Riser, ½ NPT Male/Female, Gun Metal CX-685B-GM 24" Brass Riser, ½ NPT Male/Female, Gun Metal

#### **Mounting Canopies**

CX-705B-GM Brass Flat Canopy, 1/2 NPT, Gun Metal CX-709B-GM Brass Raised Canopy, ½ NPT, Gun Metal CX-718B-GM 5" Brass Canopy, 3-Hole ½ NPT, Gun Metal CX-719B-GM Brass Tree Mounting Bracket, 1/2" NPT, Gun Metal CX-720-BR

CX-721-BR

CX-722-BR

CX-723-BR



FAX.

(800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500

Cast Brass



# **ACCESSORIES SHEET**

E-Mail: sales@coronalighting.com Directional Lights

# PRODUCT #: CL-528B-GM

#### Mounting Posts For Sign Light & **Path Light Applications**

CX-678B-GM 24" Brass Single Head Post, Gun Metal CX-679B-GM 24" Brass Double Head Post, Gun Metal CX-690B-GM 18" Brass Single Head Post, Gun Metal CX-693B-GM 18" Brass Double Head Post, Gun Metal

•CX-718B-GM (Mounting Canopies pg 2) is required for sign light installation.



#### **Cable Connectors**

CX-854 Direct Burial Silicone Filled Wire Nut, Tan

CX-858 Speedy Cable Connector, Supply Cable up to 10-2, Black

CX-839 Universal cable connector, Supply cable up to 8-2,

one/Pack Black



#### Special Lenses & Honeycomb Louvers

| CX-238    | MR-16 Snap-on holder, Silver Plated |
|-----------|-------------------------------------|
| CX-239    | MR-16 honeycomb louver, Black       |
| CX-240-AM | MR-16 color lens, Amber             |
| CX-240-BL | MR-16 color lens, Blue              |
| CX-240-GR | MR-16 color lens, Green             |
| CX-240-RD | MR-16 color lens, Red               |
| CX-240-YL | MR-16 color lens, Yellow            |
| GX-241    | MR-16 lens, Linear Spread           |
| CX-242    | MR-16 lens, Frosted                 |
| CX-243    | MR-16 lens, Prismatic               |

For MR-16 Lenses and Louvers, you will need the CX-238

