

Finish:

Lens: Socket:

Lamp:

Wiring:

SPECIFICATION SHEET

1633 Staunton Ave Los Angeles, CA 90021 FAX. TEL. (800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

Housing & Shroud: Corrosion Resistant Cast Brass.

connector (CX-839) and silicone filled wire nut (CX-854) are available from Corona Lighting.

Fixture Specifications:

Directional Lights

1

e	Specifications:		
& Shroud: Corrosion Resistant Cast Brass. Shroud is adjustable and extendable.		Gasket:	Silicone gasket for water tight sealing.
		Knuckle:	Adjustable cast brass knuckle with thumb screw
AB finish will vary du	AB- Antique Bronze. Natural toning process. B finish will vary due to artistic process.		and $\frac{1}{2}$ " NPT threaded male hub on bottom.
	lso available in GM - Gun Metal finish	Mounting Spike:	Standard injection molded spike with ½" NPT threaded female hub.
Clear and heat resistant tempered flat glass Top grade fixed ceramic bi-pin socket, with lamp retension clip to securely hold lamp in place.		Electrical Notes:	A remote 12V transformer is required. Options are
			available from Corona Lighting. Voltage range for LED lamps are 9V-17V.
	2V, MR-16, 50W max. wailable in LED (3.5W & 5W) or without lamp.		Proper grease/lubricant is suggested on threaded parts during installation process.
S	See the Lamp Guide below for more information.	Warranty:	Limited lifetime warranty on fixture housing agains manufacturer's defects.
Fixture is prewired with a 5-ft 18-2 SPT2-W direct burial cord. Wire connector sold seperately. Universal			

/~23/" Adlustable Shroud 81/2" 3.5W and 5W JOB INFORMATION AVAILABLE LED LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects) BEAM COLOR & HALOGEN RATED LAMP NUMBER SPREAD WATTS LUMEN TEMP. HOURS EQUIVALENT DATE: TYPE: L-ED16-3W-SP 15° Spot 2700K 50,000 25 Watt 3.5 270 JOB NAME & ADDRESS: L-ED16-3W-FL 3.5 45° Flood 270 2700K 50,000 25 Watt L-ED16-3W-WF 60° Wide Flood 2700K 25 Watt 3.5 270 50 000 PRODUCT #: L-ED16-5W-SP 5 15° Spot 350 2700K 50,000 40 Watt L-ED16-5W-FL 5 45° Flood 350 2700K 50,000 40 Watt TOTAL QUANTITY: L-ED16-5W-WF 5 60° Wide Flood 350 2700K 50,000 40 Watt L-ED16-COB5W-SP 5 15° Spot 450 2700K 50.000 50 Watt LAMP TYPE & WATTAGE: L-ED16-COB5W-FL 38° Flood 2700K 50,000 50 Watt 5 450 TRANSFORMER: L-ED16-COB5W-WF 2700K 50,000 50 Watt 5 60° Wide Flood 450 L-ED16-COB5W-SP3K 5 15° Spot 470 3000K 50,000 50 Watt CONTRACTOR:

Single color MR-16 LED available in AMBER, BLUE, GREEN, PURPLE, RED and VIOLET

When ordering LED lamp with a fixture your part number should follow the format below:

38° Flood

60° Wide Flood

•CL - product # lamp wattage - lamp angle

5

5

L-ED16-COB5W-FL3K

L-ED16-COB5W-WF3K

Example: CL-532B-AB-L-ED16-5W-FL FL CL - 532B-AB - L-ED16 -5W -

470

470

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.

3000K

3000K

50,000

50.000

50 Watt

50 Watt

SPECIFIER:



ACCESSORIES SHEET

PRODUCT # : CL-532B-AB

Mounting Pedestals

mounting	odootalo
CX-601-BK	1" PVC Mounting Pedestal, ½" NPT, Black
CX-601-VG	1" PVC Mounting Pedestal, 1/2" NPT, Verde Green
CX-603-BK	3" PVC Mounting Pedestal, ½" NPT Female Brass Hub on top, Black
CX-603-VG	3" PVC Mounting Pedestal, $^{1\!\!/}_2$ " NPT Female Brass Hub on top, Verde Green
	≺−−−− 18"−−−►



1" PVC Adjustable Mounting Pedestal, ½" NPT, Black
1" PVC Cap, ½" NPT, Black
1" PVC Cap, 1/2" NPT, Verde Green
2" PVC Cap, ½" NPT, Black
2" PVC Cap, 1/2" NPT, Verde Green
3" PVC Cap, 1/2" NPT Female Brass Hub, Black
3" PVC Cap, $1\!\!\!/_2$ " NPT Female Brass Hub, Verde Green

1633 Staunton Ave Los Angeles, CA 90021 TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

•Directional Lights

Cast Brass

Ground Spikes

CX-642-BK	8.5" ABS Spike, ½" NPT, Black
CX-642-BZ	8.5" ABS Spike, 1/2" NPT, Bronze
CX-643-BZ	8.5" ABS Spike, ½" NPT, Bronze



CX-647-BK

CX-646-BK	8" ABS Spike, ½" NPT, Black
CX-646-BR	8" ABS Spike, ½" NPT, Natural Brass
CX-646-SS	8" ABS Spike, 1/2" NPT, Stainless Steel
CX-647-BK	10.5" Heavy Duty ABS Spike, ½" NPT, Black

Mounting Risers

CX-682B-AB	6" Brass Riser, ½ NPT Male/Female, Antique Bronze
CX-683B-AB	12" Brass Riser, $\frac{1}{2}$ NPT Male/Female, Antique Bronze
CX-684B-AB	18" Brass Riser, 1/2 NPT Male/Female, Antique Bronze
CX-685B-AB	24" Brass Riser, ½ NPT Male/Female, Antique Bronze

Mounting Canopies

11/

·**2**³⁄₄"-

CX-709B-AB

CX-705B-AB	Brass Flat Canopy, ½ NPT, Antique Bronze
CX-709B-AB	Brass Raised Canopy, ½ NPT, Antique Bronze
CX-718B-AB	5" Brass Canopy, 3-Hole ½ NPT, Antique Bronze
CX-719B-AB	Brass Tree Mounting Bracket, 1/2" NPT, Antique Bron
CX-720-BR	Brass Tree mount Canopy with 9" Rubber Strap stretches to 14, Natural Brass
CX-721-BR	Brass Tree mount Canopy with 15" Rubber Strap stretches to 22", Natural Brass
CX-722-BR	Brass Tree mount Canopy with 22" Rubber Strap stretches to 33", Natural Brass
CX-723-BR	Brass Tree mount Canopy with 31" Rubber Strap stretches to 45", Natural Brass



-**2**⁷/8" -

CX-705B-AB

WWW.CORONALIGHTING.COM
ARCHITECTURAL GRADE SERIES

ACCESSORIES SHEET

PRODUCT # : CL-532B-AB

Mounting Posts For Sign Light & Path Light Applications

CX-678B-AB	24" Brass Single Head Post, Antique Bronze
CX-679B-AB	24" Brass Double Head Post, Antique Bronze
CX-690B-AB	18" Brass Single Head Post, Antique Bronze
CX-693B-AB	18" Brass Double Head Post, Antique Bronze

•CX-718B-AB (Mounting Canopies pg 2) is required for sign light installation.



E-Mail: sales@coronalighting.com

•Directional Lights

Cast Brass

Cable Connectors

CX-854	Direct Burial Silicone Filled Wire Nut, Tan
CX-858	Speedy Cable Connector, Supply Cable up to 10-2, Black
CX-839	Universal cable connector, Supply cable up to 8-2, one/Pack Black



Special Lenses & Honeycomb Louvers

CX-238	MR-16 Snap-on holder, Silver Plated
CX-239	MR-16 honeycomb louver, Black
CX-240-AM	MR-16 color lens, Amber
CX-240-BL	MR-16 color lens, Blue
CX-240-GR	MR-16 color lens, Green
CX-240-RD	MR-16 color lens, Red
CX-240-YL	MR-16 color lens, Yellow
CX-241	MR-16 lens, Linear Spread
CX-242	MR-16 lens, Frosted
CX-243	MR-16 lens, Prismatic

For MR-16 Lenses and Louvers, you will need the CX-238



