

1633 Staunton Ave Los Angeles, CA 90021 FAX. TEL. (800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

PRODUCT # : CL-106-BT-GM

• Down Lights

SPECIFICATION SHEET

Cast Brass

Fixture Specifications:			
Housing:	Corrosion Resistant Cast Brass	Gasket:	Silicone double gasketed for water-tight sealing
Finish:	GM - Gun Metal Natural Toning process, color may vary.	Knuckle:	Swivel cast brass knuckle with thumb screw and $\frac{1}{2}$ " NPT threaded male hub on bottom.
Lens:	Also availble in AB - Antique Bronze Clear, Convex Glass Lens. 15° & 60° reflectors included (see page 2)	Wiring:	Fixture is prewired with a 10ft 18-2 SPT-2W direct burial cord. Wire connector sold seperately. Universal connector (CX-839), and silicone filled wire nut (CX-854) are available from Corona Lighting.
Light Source:	Replacable 1-6W RGB LED module. Lumen output is between 15LM - 450LM. Standard 38° beam spread, with 15° & 60° options also included.	Mounting:	Brass mounting bracket with ½" NPT threaded female hub. CX-709B Brass Canopy mounting is also available.
LED Features	CCT Options: Presets: 2700K, 3000K, 4000K, 5000K RGB : Unlimited color wheel options & quick presets. Dimming: Every color choice Scenes: Customizable scenes with up to 8 colors. Compatibility: Amazon's Alexa and Google Home Music: The lights will follow music collected by a	Electrical Notes:	A remote 12V transformer is required. Options are available from Corona Lighting. Voltage range for LED module is 10V-15V. Proper grease/lubricant is suggested on threaded parts during installation process.
	phone microphone.	Warranty:	Lifetime limited warranty on fixture housing. Ten (10) years warranty on LED module.
121	GM Finish Shown	E D BRATED	$ \begin{array}{c} 1^{1/2}" \\ 4^{3/4}" \\ 4^{3/4}" \\ 1^{3/8}" \\ 2^{1/2}" \end{array} $
	SMART ACCESSORIES		



