

TEL.

(800) 727-9262

(800) 727-9957 (213) 747-4500

(213) 747-3234



Faceplate:

ARCHITECTURAL GRADE SERIES

SPECIFICATION SHEET

Wiring:

Mounting:

Electrical Notes:

Applications:

Warranty:

E-Mail: sales@coronalighting.com

PRODUCT #: CL-311-BR

Fixture Specifications:

Housing: Corrosion resistant cast brass.

> Cast brass with 316 marine grade stainless steel screws.

Finish: **BR- Natural Brass**

Lens: Clear, tempered, and heat resistant glass. Socket: Top grade fixed ceramic bi-pin socket.

Lamp: 12V, MR-16, 50W max.

Available in LED (3.5W & 5W) without lamp. See the Lamp Guide below for more information.

Gasket: Silicone "O" ring seals faceplate to housing

providing water tight protection.

Underwater

Cast Brass

Fixture is prewired with a 30-ft 16-2 SJT-W water

resistant cord. Longer cord length is also available. Fully adjustable arms with thumb screws to provide

light aiming. Fixture is mounted on a heavy duty brass bracket for a firm and stable underwater

placement.

A remote 12V transformer is required. Options are

available from Corona Lighting.

Voltage range for LED lamps are 9V-17V.


To be used in fountains, ponds, and waterfalls. Do not use in swimming pools, lakes or spas.

Limited lifetime warranty on fixture against

manufacturer's defects.







JOB INFORMATION

JOB NAME & ADDRESS:

LAMP TYPE & WATTAGE:

DATE:

TYPE:

PRODUCT #: **TOTAL QUANTITY:**

TRANSFORMER: CONTRACTOR: SPECIFIER:

| AVAILABLE LED LAMPS | (Corona LED lamps have a five | (5) year limited warranty | against manufacturer's defects) |
|---------------------|--------------------------------------|---------------------------|---------------------------------|
| | | | |

| | | BEAM | Λ | COLOR & | RATED | HALOGEN | | |
|--|----------------|----------------|-------|---------|---------|------------|--|--|
| LAMP NUMBER | WATTS | SPREAD | LUMEN | TEMP. | HOURS | EQUIVALENT | | |
| L-ED16-3W-SP 3.5 L-ED16-3W-FL 3.5 | | 15° Spot | 270 | 2700K | 50,000 | 25 Watt | | |
| | | 45° Flood | 270 | 2700K | 50,000 | 25 Watt | | |
| L-ED16-3W-WF | 3.5 | 60° Wide Flood | 270 | 2700K | 50,000 | 25 Watt | | |
| L-ED16-5W-SP 5 L-ED16-5W-FL 5 | | 15° Spot | 350 | 2700K | 50,000 | 40 Watt | | |
| | | 45° Flood | 350 | 2700K | 50,000 | 40 Watt | | |
| L-ED16-5W-WF | 60° Wide Flood | 350 | 2700K | 50,000 | 40 Watt | | | |
| L-ED16-COB5W-SP | 5 | 15° Spot | 450 | 2700K | 50,000 | 50 Watt | | |
| L-ED16-COB5W-FL 5 | | 38° Flood | 450 | 2700K | 50,000 | 50 Watt | | |
| L-ED16-COB5W-WF | 5 | 60° Wide Flood | 450 | 2700K | 50,000 | 50 Watt | | |
| L-ED16-COB5W-SP3K | 5 | 15° Spot | 470 | 3000K | 50,000 | 50 Watt | | |
| L-ED16-COB5W-FL3K 5 L-ED16-COB5W-WF3K 5 | | 38° Flood | 470 | 3000K | 50,000 | 50 Watt | | |
| | | 60° Wide Flood | 470 | 3000K | 50,000 | 50 Watt | | |

■ Single color MR-16 LED available in AMBER, BLUE, GREEN, PURPLE, RED and VIOLET

CL - 311-BR - L-ED16 -

| • \ | Nhen | ordering | LED | lamp | with | a fixture | your | part | num | ber s | shoule | d fo | llow | the | format | be | low: |
|-----|------|----------|-----|------|------|-----------|------|------|-----|-------|--------|------|------|-----|--------|----|------|
| | | | | | | | | | | | | | | | | | |

Example: CL-311-BR-L-ED16-5W-FL

Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



ACCESSORIES SHEET

1633 Staunton Ave Los Angeles, CA 90021

TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

PRODUCT #: CL-311-BR

Underwater

• Cast Brass

Special Lenses & Honeycomb Louvers

CX-238 MR-16 Snap-on holder, **Silver Plated**CX-239 MR-16 honeycomb louver, **Black**

CX-240-AM MR-16 color lens, Amber
CX-240-BL MR-16 color lens, Blue
CX-240-GR MR-16 color lens, Green
CX-240-RD MR-16 color lens, Red
CX-240-YL MR-16 color lens, Yellow
CX-241 MR-16 lens, Linear Spread

CX-242 MR-16 lens, **Frosted**CX-243 MR-16 lens, **Prismatic**

For MR-16 Lenses and Louvers, you will need the CX-238

