

**SPECIFICATION SHEET** 

 1633 Staunton Ave

 Los Angeles, CA
 90021

 TEL.
 FAX.

 (800)
 727-9262
 (800)
 727-9957

 (213)
 747-4500
 (213)
 747-3234

E-Mail: sales@coronalighting.com

1

PROD									
Fixture \$	Specification	าร:							
Housing:	Heavy Duty corrosic with self-leveling ac			steel	Wiring:		cord. Wire connec	ctor sold se	a 12 inch direct buria perately. Silicone fille e from Corona Lightir
Faceplate:	Solid brass, fitted to silicone gasket.	housing wit	h a		Mounting	g:	Recessed mount	back box. E	Best used in concrete
Finish:	Stamped brass available in <b>AB</b> - Antique Bronze, <b>GM</b> - Gun Metal and <b>SI</b> - Silver Plated. AB finish will vary due to artistic process. Also available in <b>BK</b> , <b>BZ</b> , <b>RC</b> , <b>RT</b> , <b>WH</b>				Electrica	al Notes:	brick and other masonry, with 3x ½" NPT inlets. A remote 12V transformer is required. Options are available from Corona Lighting. Voltage range for LED lamps are 8V-21V.		
Lens:	High impact white p	olycarbonate	е		Warranty	<i>ı</i> :			l lifetime warranty on
Socket:	Two S.C. Bayonet s reflector.	Two S.C. Bayonet sockets, attached to aluminum reflector.					fixture housing and faceplate against manufacturer' defects. <b>BK, BZ, RT</b> and <b>WH</b> - Five year warranty on fixture		
Lamp:	Two 12V, S.C. Bayo Available in 2xLED See the Lamp Guid	(2W & 2.5W	) or without				housing and facer defects.	plate agains	st manufacturer's
Gasket:	Silicone gasket, sea Providing weather t		0						
	CX-733B-L-	EDBA-2W Sho	own Self-L	eveling M	← mo ounting B	faceplate unting scre racket	W Self leveling the mounting alignment of 8"	g box allo	
	CX-733B-L-	EDBA-2W Sha	0	eveling M (enlarged	← mo	aracket Tracket 2" ↓	the mounting	g box allo	w for proper
			Ø	eveling M (enlarged	ounting B for detail)	aracket Tracket 2" ↓ W	the mounting alignment of 8"	g box allo the facep 0 9" -	w for proper blate.
	E LED LAMPS (Coron	a LED lamps ha BEA	N ve a five (5) yea	eveling M (enlarged 2x 2 coLOR &	ounting B for detail) E D N & 2.5 ty against manu RATED	aracket	the mounting alignment of 8" (s) JOB INFORM	g box allo the facep 0 9" -	w for proper blate.
	E LED LAMPS (Coron R WATTS	a LED lamps ha BEA SPREAD 360°	N ve a five (5) yea M LUMEN 200	eveling M (enlarged 2x 2 ar limited warran COLOR & TEMP. 2700K	mo ounting B for detail) E D W & 2.5 ty against manu RATED HOURS 25,000	aracket	the mounting alignment of 8" (*) (*) (*) (*) (*) (*) (*) (*) (*) (*)	g box allo the facep 	w for proper plate.
2" ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓	E LED LAMPS (Coron R WATTS 2 2.5	a LED lamps ha BEA SPREAD	N ve a five (5) yea M LUMEN	eveling M (enlarged) 2x 2 ar limited warran COLOR & TEMP.	ounting B for detail) ED W & 2.5 ty against manu RATED HOURS	aunting scree sracket	the mounting alignment of 8" (s) JOB INFORM	g box allo the facep 	w for proper plate.
2" - - - - - - - - - - - - -	E LED LAMPS (Coron R WATTS 2 2.5 K 2 -3K 2.5	a LED lamps ha BEA SPREAD 360° 180° 360° 180°	Ve a five (5) yea M LUMEN 200 240 210 250	eveling M (enlarged 2x 2) ar limited warran COLOR & TEMP. 2700K 2700K 2700K 3000K 3000K	mo ounting B for detail) E D W & 2.5 ty against manu RATED HOURS 25,000 25,000 25,000 25,000	aunting scree aracket	the mounting alignment of 8" (*) (*) (*) (*) (*) (*) (*) (*) (*) (*)	g box allo the facep 	w for proper plate.
2" ↓ 2"	E LED LAMPS (Coron R WATTS 2 2 2.5 K 2 -3K 2.5 2	a LED lamps ha BEA SPREAD 360° 180° 360°	N ve a five (5) yea M LUMEN 200 240 210	eveling M (enlarged 2x 2) ar limited warran COLOR & TEMP. 2700K 2700K 2700K 3000K	mo ounting B for detail) E D W & 2.5 ty against manu RATED HOURS 25,000 25,000 25,000	aunting scree aracket	the mounting alignment of 8"          8"         Image: system of the mounting alignment of the mounting alignment of the mount of t	g box allo the facep 0 9" - <u>MATION</u>	w for proper plate.
2" ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓	E LED LAMPS (Coron R WATTS 2 2 2.5 K 2 -3K 2.5 2	a LED lamps ha BEA SPREAD 360° 180° 360° 180° 360°	Ve a five (5) yea M LUMEN 200 240 210 250 170	eveling M (enlarged 2x 2) ar limited warran COLOR & TEMP. 2700K 2700K 2700K 3000K 3000K	mo ounting B for detail) E D W & 2.5 ty against manu RATED HOURS 25,000 25,000 25,000 25,000	aunting scree aracket	the mounting alignment of 8" 8" 8" 8" 8" 50 50 50 50 50 50 50 50 50 50 50 50 50	g box allo the facer 9" - MATION DDRESS:	w for proper plate.
2" ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓	E LED LAMPS (Coron R WATTS 2 2.5 3 4 2.5 3 4 2 -3 4 2 -3 4 2 -3 4 2 -3 5 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -2 -3 -2 -2 -3 -2 -3 -2 -3 -2 -2 -3 -2 -2 -3 -2 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -3 -2 -3 -3 -2 -3 -3 -2 -3 -3 -3 -2 -3 -3 -2 -3 -3 -3 -3 -3 -3 -3 -3 -3 -3	a LED lamps ha BEA SPREAD 360° 180° 360° 180° 360°	Ve a five (5) yea M LUMEN 200 240 210 250 170	eveling M (enlarged 2x 2) ar limited warran COLOR & TEMP. 2700K 2700K 2700K 3000K 3000K	mo ounting B for detail) E D W & 2.5 ty against manu RATED HOURS 25,000 25,000 25,000 25,000	aunting scree aracket	the mounting alignment of 8" © (s) JOB INFORM T TYPE: JOB NAME & AU PRODUCT #: TOTAL QUANTIT LAMP TYPE & W	g box allo the facep 9" - <u>ATION</u> DDRESS:	w for proper plate.
2" 2" 4 2" 4 2" 4 4 4 4 4 4 4 4 4 4 4 4 4	E LED LAMPS (Coron R WATTS 2 2.5 3 4 2.5 3 4 2 -3 4 2 -3 4 2 -3 4 2 -3 5 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -2 -3 -2 -2 -3 -2 -3 -2 -3 -2 -2 -3 -2 -2 -3 -2 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -3 -2 -3 -3 -2 -3 -3 -2 -3 -3 -3 -2 -3 -3 -2 -3 -3 -3 -3 -3 -3 -3 -3 -3 -3	a LED lamps ha BEA SPREAD 360° 180° 360° 180° 360°	Ve a five (5) yea M LUMEN 200 240 210 250 170	eveling M (enlarged 2x 2) ar limited warran COLOR & TEMP. 2700K 2700K 2700K 3000K 3000K	mo ounting B for detail) E D W & 2.5 ty against manu RATED HOURS 25,000 25,000 25,000 25,000	aunting scree aracket	the mounting alignment of 8"          8"         Image: state sta	g box allo the facep 9" - <u>ATION</u> DDRESS:	w for proper plate.
2" 2" 4 2" 4 2" 4 4 4 4 4 4 4 4 4 4 4 4 4	E LED LAMPS (Coron R WATTS 2 2.5 3 4 2.5 3 4 2 -3 4 2 -3 4 2 -3 4 2 -3 5 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -2 -3 -2 -2 -3 -2 -3 -2 -3 -2 -2 -3 -2 -2 -3 -2 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -3 -2 -3 -3 -2 -3 -3 -2 -3 -3 -3 -2 -3 -3 -2 -3 -3 -3 -3 -3 -3 -3 -3 -3 -3	a LED lamps ha BEA SPREAD 360° 180° 360° 180° 360°	Ve a five (5) yea M LUMEN 200 240 210 250 170	eveling M (enlarged 2x 2) ar limited warran COLOR & TEMP. 2700K 2700K 2700K 3000K 3000K	mo ounting B for detail) E D W & 2.5 ty against manu RATED HOURS 25,000 25,000 25,000 25,000	aunting scree aracket	the mounting alignment of 8"	g box allo the facep 9" - <u>ATION</u> DDRESS:	w for proper plate.
2" 2" 4 2" 4 2" 4 4 4 4 4 4 4 4 4 4 4 4 4	E LED LAMPS (Coron R WATTS 2 2.5 3 4 2.5 3 4 2 -3 4 2 -3 4 2 -3 4 2 -3 5 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -2 -3 -2 -2 -3 -2 -3 -2 -3 -2 -2 -3 -2 -2 -3 -2 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -2 -3 -3 -2 -3 -3 -2 -3 -3 -2 -3 -3 -3 -2 -3 -3 -2 -3 -3 -3 -3 -3 -3 -3 -3 -3 -3	a LED lamps ha BEA SPREAD 360° 180° 360° 180° 360°	Ve a five (5) yea M LUMEN 200 240 210 250 170	eveling M (enlarged 2x 2) ar limited warran COLOR & TEMP. 2700K 2700K 2700K 3000K 3000K	mo ounting B for detail) E D W & 2.5 ty against manu RATED HOURS 25,000 25,000 25,000 25,000	aunting scree aracket	the mounting alignment of 8"          8"         Image: state sta	g box allo the facep 9" - <u>ATION</u> DDRESS:	w for proper plate.



Example: CL-366B-AB-L-EDBA-2W-3K

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



## **ACCESSORIES SHEET**

 1633 Staunton Ave


 Los Angeles, CA 90021

 TEL.
 FAX.

 (800) 727-9262
 (800) 727-9957

 (213) 747-4500
 (213) 747-3234

E-Mail: sales@coronalighting.com



Brick Lights

CX-854

**Cable Connector** 

Solid Brass

## Faceplates


CX-878B Brass, lensed faceplate with white acrylic lens.

Finishes: AB- Antique Bronze, GM- Gun Metal, and SI- Silver Plated

CX-878 Aluminum, lensed faceplate with white acrylic lens.

Finishes: Available in **BK**- Black, **BZ**- Bronze, **RT**- Rust, and **WH**- White

CX-878C-RC Copper, lensed faceplate with white acrylic lens. Finish: Available in **RC**- Raw Copper





Direct Burial Silicone Filled Wire Nut, Tan

## **Mount Box**

CX-733B

Steel Mount Box

