

TEL.

(800) 727-9262

(800) 727-9957

(213) 747-3234 (213) 747-4500



ARCHITECTURAL GRADE SERIES

SPECIFICATION SHEET

Gasket:

E-Mail: sales@coronalighting.com

PRODUCT #: CL-514B-GM

Directional Lights

Cast Brass

Fixture Specifications:

Housing & Shroud: Corrosion Resistant Cast Brass.

Finish: GM-Gun Metal Natural toning process.GM finish will

vary due to artistic process. Also available in AB, and RC.

Lens: Clear and heat resistant convex glass.

Socket: Top grade loose bi-pin socket, with spring

loaded design.

Lamp: 12V, MR-16, 35W max.

> Available in LED (3.5W & 5W) or without lamp. See the Lamp Guide below for more information.

Wiring: Fixture is prewired with a 5-ft 18-2 SPT2-W direct

burial cord. Wire connector sold seperately.

Universal connector (CX-839) and silicone filled wire nut (CX-854) are available from Corona Lighting.

Silicone gasket for water tight sealing.

Knuckle: Adjustable cast brass knuckle with thumb screw

and 1/2" NPT threaded male hub on bottom.

Mounting Spike: Standard injection molded spike with 1/2" NPT

threaded female hub.

Electrical Notes: A remote 12V transformer is required. Options are

available from Corona Lighting.


Voltage range for LED lamps are 9V-17V. Proper grease/lubricant is suggested on threaded parts during installation process.

Warranty: Limited lifetime warranty on fixture housing against

manufacturer's defects.







AVAILABLE LED LAMPS (Co	Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)
-------------------------	---

		BEAM		COLOR &	RATED	HALOGEN
LAMP NUMBER	WATTS	SPREAD	LUMEN	TEMP.	HOURS	EQUIVALENT
L-ED16-3W-SP	3.5	15° Spot	270	2700K	50,000	25 Watt
L-ED16-3W-FL	3.5	45° Flood	270	2700K	50,000	25 Watt
L-ED16-3W-WF	3.5	60° Wide Flood	270	2700K	50,000	25 Watt
L-ED16-5W-SP	5	15° Spot	350	2700K	50,000	40 Watt
L-ED16-5W-FL	5	45° Flood	350	2700K	50,000	40 Watt
L-ED16-5W-WF	5	60° Wide Flood	350	2700K	50,000	40 Watt
L-ED16-COB5W-SP	5	15° Spot	450	2700K	50,000	50 Watt
L-ED16-COB5W-FL	5	38° Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-WF	5	60° Wide Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-SP3K	5	15° Spot	470	3000K	50,000	50 Watt
L-ED16-COB5W-FL3K	5	38° Flood	470	3000K	50,000	50 Watt
L-ED16-COB5W-WF3K	5	60° Wide Flood	470	3000K	50,000	50 Watt
Single color MR-16 LED available in AMBER, BLUE, GREEN, PURPLE, RED and VIOLET						

JOB INFORMATION

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

• When ordering LED lamp with a fixture your part number should follow the format below:

• CL - product # - lamp - wattage - lamp angle CL - 514B-GM - L-ED16 - 5W -FL

Example: CL-514B-GM-L-ED16-5W-FL

Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



WWW.CORONALIGHTING.COM

ARCHITECTURAL GRADE SERIES

ACCESSORIES SHEET

1633 Staunton Ave Los Angeles, CA 90021

FAX. (800) 727-9957 (800) 727-9262

(213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

Cast Brass

PRODUCT #: CL-514B-GM

Mounting Pedestals

CX-601-BK 1" PVC Mounting Pedestal, 1/2" NPT, Black


CX-601-VG 1" PVC Mounting Pedestal, 1/2" NPT, Verde Green

CX-603-BK 3" PVC Mounting Pedestal, 1/2" NPT Female Brass Hub

on top, Black

CX-603-VG 3" PVC Mounting Pedestal, ½" NPT Female Brass Hub

on top, Verde Green



CX-604-BK 1" PVC Adjustable Mounting Pedestal, 1/2" NPT, Black

CX-621-BK 1" PVC Cap, 1/2" NPT, Black

1" PVC Cap, ½" NPT, Verde Green CX-621-VG

CX-622-BK 2" PVC Cap, 1/2" NPT, Black

CX-622-VG 2" PVC Cap, 1/2" NPT, Verde Green

CX-624-BK 3" PVC Cap, 1/2" NPT Female Brass Hub, Black

CX-624-VG 3" PVC Cap, 1/2" NPT Female Brass Hub, Verde Green

Mounting Canopies

CX-705B-GM Brass Flat Canopy, 1/2 NPT, Gun Metal CX-709B-GM Brass Raised Canopy, 1/2 NPT, Gun Metal CX-718B-GM 5" Brass Canopy, 3-Hole ½ NPT, Gun Metal CX-719B-GM Brass Tree Mounting Bracket, 1/2" NPT, Gun Metal CX-720-BR Brass Tree mount Canopy with 9" Rubber Strap stretches to 14, Natural Brass CX-721-BR Brass Tree mount Canopy with 15" Rubber Strap stretches to 22", Natural Brass

CX-722-BR Brass Tree mount Canopy with 22" Rubber Strap

stretches to 33", Natural Brass

CX-723-BR Brass Tree mount Canopy with 31" Rubber Strap

stretches to 45", Natural Brass

23/4" 27/8" -CX-709B-GM CX-705B-GM

Directional Lights **Ground Spikes**

CX-642-BK 8.5" ABS Spike, 1/2" NPT, Black

CX-642-BZ 8.5" ABS Spike, 1/2" NPT, Bronze CX-643-BZ 8.5" ABS Spike, 1/2" NPT, Bronze



CX-647-BK

CX-646-BK 8" ABS Spike, 1/2" NPT, Black

8" ABS Spike, 1/2" NPT, Natural Brass CX-646-BR CX-646-SS 8" ABS Spike, 1/2" NPT, Stainless Steel

CX-647-BK 10.5" Heavy Duty ABS Spike, 1/2" NPT, Black

Mounting Risers

CX-682B-GM 6" Brass Riser, ½ NPT Male/Female, **Gun Metal** CX-683B-GM 12" Brass Riser, ½ NPT Male/Female, Gun Metal CX-684B-GM 18" Brass Riser, ½ NPT Male/Female, Gun Metal CX-685B-GM 24" Brass Riser, ½ NPT Male/Female, Gun Metal





FAX.

Cast Brass



(800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500



ACCESSORIES SHEET

E-Mail: sales@coronalighting.com

PRODUCT #: CL-514B-GM

Mounting Posts For Sign Light & **Path Light Applications**

CX-678B-GM 24" Brass Single Head Post, Gun Metal CX-679B-GM 24" Brass Double Head Post, Gun Metal CX-690B-GM 18" Brass Single Head Post, Gun Metal CX-693B-GM 18" Brass Double Head Post, Gun Metal

•CX-718B-GM (Mounting Canopies pg 2) is required for sign light installation.



Directional Lights

Cable Connectors

CX-854 Direct Burial Silicone Filled Wire Nut, Tan

CX-858 Speedy Cable Connector, Supply Cable up to 10-2, Black

CX-839 Universal cable connector, Supply cable up to 8-2,

one/Pack Black



Special Lenses & Honeycomb Louvers

CX-238	MR-16 Snap-on holder, Silver Plated
CX-239	MR-16 honeycomb louver, Black
CX-240-AM	MR-16 color lens, Amber
CX-240-BL	MR-16 color lens, Blue
CX-240-GR	MR-16 color lens, Green
CX-240-RD	MR-16 color lens, Red
CX-240-YL	MR-16 color lens, Yellow
CX-241	MR-16 lens, Linear Spread
CX-242	MR-16 lens, Frosted
CX-243	MR-16 lens, Prismatic

• For MR-16 Lenses and Louvers, you will need the CX-238

